

W1 - Wipers wall/floor /standard system, W2 -Wipers combi roll system, W3 - Wiper pak system

Tork Heavy-Duty Cleaning Cloth



Article	530137
System	W1 - Wipers wall/floor /standard system, W2 - Wipers combi roll system, W3 - Wiper pak system
Colour	White
Core inside diameter	7.1 cm
Embossing	No
Number of sheets	280
Ply	1
Print	No
Roll diameter	25 cm
Roll length	106.4 m
Roll width	32 cm
Sheet length	38 cm

The multipurpose Tork Heavy-Duty Cleaning Cloth is highly absorbent, thick and very durable, withstanding hard scrubbing without falling apart. It works with most solvents and removes oil, grease, water and stubborn spots quickly and effectively, while protecting hands from heat and metal scraps. This cloth fits in the Tork Floor or Wall Stand dispensers, developed for safety and efficiency, and the Tork Maxi Centrefeed or Boxed Combi Roll Dispenser, designed for single hand dispensing.

Key benefits:

- Compatible with most chemical solvents: Picks up and releases solvents more efficiently than textile productsthereby reducing consumption

- Heavy-Duty design protects your hands from heat and metal scraps

- Reusable, strong, durable wipe - excellent rental towel and rag replacement

- Heavy-Duty design protects your hands from heat and metal scraps

- Reusable, strong, durable wipe - excellent rental towel and rag replacement

Environmental	
Polypropylene	Polypropylene or polypropene is a thermoplastic polymer made from oil. The moten resin is spun to endless fibres through spinnerets and cooled by air. The fibres form a web. Polyester
Environmental certification	Polypropylene
Article creation date and latest article revision	Date of issue: 19-04-2019 Revision date: 04-05-2021 Functional agents or additives
Tork exelCLEAN® cloths	
Cellulose Pulp	Cellulose pulp is produced either from softwood or hardwood coming from responsibly managed forests. The wood chips are boiled together with chemicals to remove the lignin between the fibres. The pulp is TCF (Totally Chlorine Free) or ECF (Elementary Chlorine Free) bleached in order to achieve a clean, bright and strong product, but also to increase the hygienic and absorbent qualities.
Polyester	Polyester fibre is produced from terephthalic acid and ethylene glycol, which react through condensation to polyester resin. The molten resin is spun to fibres through spinnerets and cooled with air. The fibers are then cut to intended fiber length.
Food Contact	This product fulfills the legislative requirements for Food Contact materials, confirmed by external certification performed by a third party. The product is safe for wiping food contact surfaces and may also come occasionally into contact with foodstuffs for a short period of time. This product is certified for FSC®.
Raw materials	
Functional agents and additives	Functional additives could be wet strength agent, antistatic agent and wetting additives/tensides.
Essity UK Ltd, Southfields Road, Dunstable, Bedfordshire LU6 3EJ, United Kingdom	
Packaging	Fulfilment of Packaging and Packaging Waste Directive (94/62/EC): Yes Cellulose Pulp
Disposal/destruction of used product	This product is mainly used for industrial processes. When used in industrial processes the product might through use be contaminated with different substances. This will determine how the used product will be handled/disposed of/destructed. The product itself is suitable for incineration. If used in industrial processes contact local authorities before destruction.
Production	This product is produced at SUAMEER mill, NL and certified according to ISO 9001 and ISO 14001 (Environmental management systems).

Contact

James Beattie Deb Disposables Ltd - 1298985 Business phone: 0161 872 3531 Business mobile phone: 0161 872 3531 E-mail: james@deb-disposables.co.uk