

### EP08 - Corded PU Foam Ear Plug (200 pairs)

**Collection:** Ear Plugs

**Range:** PPE

**Materials:** PU Foam, PVC

**Inner Pack:** 200

**Outer Carton:** 10

#### Product information

Disposable PU ear plug. The tapered shape ensures a comfortable fit inside the ear canal. Corded for extra comfort and easy storage around the neck when not in use. Each pair comes inside a hygienic polybag with fitting instructions.

#### PPE

Portwest Head PPE range applies the latest standards to deliver the highest level of protection. Comfortable and lightweight, the PPE range will ensure a pleasant wear, even for long periods of use. Your safety is our mission.

#### Standards

EN 352-2 (SNR 36dB)

ANSI S3.19 (32dB)



#### Features

- CE-CAT III
- Retail box which aids presentation for retail sales
- Corded for safe keeping
- Easy to fit
- One pair per hang cell (stored in hygienic polybag)
- Individually packed for vending machines

	Range
Orange	-

# PORTWEST®

## PRODUCT SPECIFICATION & TECHNICAL DATA

### EP08 - Corded PU Foam Ear Plug (200 pairs)

**Commodity Code: 3926909790**

#### Test House

Michael & Associates, Inc. (Notified Body No.: )

2766 W. College Ave Suite 1

PA 16801, United States

Cert No: Q1441A

ALIENOR CERTIFICATION (Notified Body No.: 2754)

ZA du Sanital

86100 , France

Cert No: 2754/1246/159/06/18/0288

#### CARTON DIMENSIONS/WEIGHT

Item	Colour	Len	Wid	Hgt	Weight (Kg)	Cubic (m <sup>3</sup> )	EAN13	DUN14
EP08ORR	Orange	65.0	35.0	33.0	0.7600	0.0751	5036108183852	15036108622419

# PORTWEST®

## PRODUCT SPECIFICATION & TECHNICAL DATA

### PERFORMANCES - SOUND ATTENUATION - EN352-2:2002

<b>EP02/EP08/EP30</b>								
<b>A</b>	<b>Frequency (Hz)</b>	<b>125</b>	<b>250</b>	<b>500</b>	<b>1000</b>	<b>2000</b>	<b>4000</b>	<b>8000</b>
<b>B</b>	Means Attenuation (dB)	36.5	34.2	39.1	37.8	39.6	44.9	46.2
<b>C</b>	Standard Deviation (dB)	4.7	4.5	4.8	5.8	4.0	6.4	6.2
<b>D</b>	Assumed Protection (dB)	31.7	29.7	34.2	32.0	35.5	38.5	40.1
<b>SNR = 36 dB H = 36 dB / M = 33 dB / L = 32 dB</b>								

### PERFORMANCES - SOUND ATTENUATION ANSI S.19-1974

Tested by Michael & Associates, Inc. – 400 Long Lane, PA Furnace, PA 16865, USA

<b>EP02/EP08</b>										
<b>A</b>	<b>Frequency (Hz)</b>	<b>125</b>	<b>250</b>	<b>500</b>	<b>1000</b>	<b>2000</b>	<b>3150</b>	<b>4000</b>	<b>6300</b>	<b>8000</b>
<b>B</b>	Means Attenuation (dB)	39.8	40.4	42.6	40.3	39.1	45.2	45.7	48.3	47.4
<b>C</b>	Standard Deviation (dB)	3.0	3.9	2.9	3.6	3.7	3.0	2.5	4.9	3.7
<b>NRR (Noise Reduction Rating) = 32 dB</b>										

EP08ORR